

**Tabla de especificaciones técnicas (Piso/techo)**

Model		MUB-24CR	MUB-36CR	MUB-48CR	MUB-60CR	
Power supply		V-Hz -Ph	208~230-60-1	208~230-60-1	208~230-60-1	208~230-60-1
Indoor fan motor	Model		YSK55-4L	YSK80-4A	YSK59-4D	YSK59-4D
	Drive	type	Direct	Direct	Direct	Direct
	Qty		1	1	2	2
	Input	W	131	172	248	248
	Output	W	65	82	117	117
	RLA	A	0.63	0.76	0.55	0.55
	LRA	A	1.03	1	0.7	0.7
	FLA	A	0.7	0.84	0.61	0.61
	Capacitor	uF	2.5uF/450V	3.5uF/450V	2.5uF/450V	2.5uF/450V
Speed(Hi/Mid/Lo)	r/min	1440/1145/950	1310/1090/940	1220/1080/980	1220/1080/980	
Fan	Type		Centrifugal	Centrifugal	Centrifugal	Centrifugal
	Number		2	3	4	4
	Diameterxlength	inch/mm	5-3/4x7-1/2 (145x190)	5-3/4x7-1/2 (145x190)	6-3/8x6-1/4 (161x160)	6-3/8x6-1/4 (161x160)
Indoor coil	Fins per inch.		14	17	16	16
	Face area	m <sup>2</sup>	0.204	0.184	0.292	0.292
		Ft <sup>2</sup>	2.2	1.98	3.14	3.14
	Coil size(WxHxD)	mm	804x254x66	905x203x66	1150x254x66	1150x254x66
		inch	31-5/8 x10 x2-5/8	35-5/8 x8 x2-5/8	45-1/4x10x2-5/8	45-1/4x10x2-5/8
	Fin type		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Number of rows		2	2	3	3
Tube O.D and type	mm/inch		9.53/ 3/8	9.53/ 3/8	9.53 / 3/8	9.53 / 3/8
			Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube
Indoor air flow (Hi/Mid/Lo)		m3/h	1200/900/700	1800/1400/1000	2000/1800/1600	2200/1800/1600
		CFM	705/530/410	1060/825/590	1176/1060/940	1295/1060/940
Indoor noise level (Hi/Mid/Lo)		dB(A)	45/43/40	45/43/40	47/46/44	47/46/44
Dimensions	Body (WxHxD)	mm	995x660x198	1285x660x198	1670x680x240	1670x680x240
		inch	39-1/4x26x7-3/4	50-5/8x26x7-3/4	65-3/4x26-7/8x9-1/2	65-3/4x26-7/8x9-1/2
	Packing (WxHxD)	mm	1089x744x296	1379x744x296	1764x760x329	1764x760x329
		inch	42-7/8x29-1/4x11-5/8	54-1/4x29-1/4x11-5/8	69-1/2x29-7/8x13	69-1/2x29-7/8x13
Piston size	Cooling	inch	0.077	0.098	0.087	0.091
		mm	1.95	2.5	2.2	2.3
	Heating	inch	—	—	—	—
		mm	—	—	—	—
Net/Gross weight		lbs	59.4/72.6	77/88	114.4/129.8	114.4/129.8
		kg	27/33	35/40	52/59	52/59
Controller			remote controller	remote controller	remote controller	remote controller
Stuffing Qty (20'/40'/40HQ)		pieces	128/264/295	97/202/226	67/137/165	67/137/165
Model (outdoor unit)			MOV-24CR	MOV-36CR	MOV-48CR	MOV-60CR
Power supply		V-Hz -Ph	208~230-60-1	208~230-60-1	208~230-60-1	208~230-60-1